



SUBSTITUTE SPECIFICATION

--- Marked Up Version ---

APPARATUS AND METHODS FOR TUBULAR MAKEUP INTERLOCK

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a divisional of co-pending U.S. ~~patent application~~ Patent Application Serial No. 09/860,127, filed May 17, 2001, which application is incorporated herein by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The present invention relates to an apparatus and methods for facilitating the connection of tubulars. More particularly, the invention relates to an interlock system for a top drive and a spider for use in assembling or disassembling tubulars.

Background of the Related Art

[0003] In the construction and completion of oil or gas wells, a drilling rig is constructed on the earth's surface to facilitate the insertion and removal of tubular strings into a wellbore. The drilling rig includes a platform and power tools such as an elevator and a spider to engage, assemble, and lower the tubulars into the wellbore. The elevator is suspended above the platform by a draw works that can raise or lower the elevator in relation to the floor of the rig. The spider is mounted in the platform floor. The elevator and spider both have slips that are capable of engaging and releasing a tubular, and are designed to work in tandem. Generally, the spider holds a tubular or tubular string that extends into the wellbore from the platform. The elevator engages a new tubular and aligns it over the tubular being held by the spider. A power tong and a spinner are then used to thread the upper and lower tubulars together. Once the tubulars are joined, the

spider disengages the tubular string and the elevator lowers the tubular string through the spider until the elevator and spider are at a predetermined distance from each other. The spider then re-engages the tubular string and the elevator disengages the string and repeats the process. This sequence applies to assembling tubulars for the purpose of drilling a wellbore, running casing to line the wellbore, or running wellbore components into the well. The sequence can be reversed to disassemble the tubular string.

[0004] During the drilling of a wellbore, a drill string is made up and is then necessarily rotated in order to drill. Historically, a drilling platform includes a rotary table and a gear to turn the table. In operation, the drill string is lowered by an elevator into the rotary table and held in place by a spider. A Kelly is then threaded to the string and the rotary table is rotated, causing the Kelly and the drill string to rotate. After thirty feet or so of drilling, the Kelly and a section of the string are lifted out of the wellbore, and additional drill string is added.

[0005] The process of drilling with a Kelly is expensive due to the amount of time required to remove the Kelly, add drill string, reengage the Kelly, and rotate the drill string. ~~Order~~ In order to address these problems, top drives were developed.

[0006] ~~Figure 1A is a side view of an upper portion of a drilling rig 100 having a top drive 200 and an elevator 120. An upper end of a stack of tubulars 130 is shown on the rig 100. The figure shows the elevator 120 engaged with a tubular 130. The tubular 130 is placed in position below the top drive 200 by the elevator 120 in order for the top drive with its gripping means to engage the tubular.~~

[0007] For example, International Application Number PCT/GB99/02203, published on February 3, 2000 discloses apparatus and methods for connecting tubulars using a top drive. In another example, Figure 1 shows a drilling rig 100 configured to connect and run casings into a newly formed wellbore 180 to line the walls thereof. As shown, the rig 100 includes a top drive 200, an elevator 120, and a spider 400. The rig 100 is built at the surface 170 of the well. The rig 100 is built at the surface 170 of the well. The rig 100 includes a travelling block 110 that is suspended by wires 150 from draw works 105

and holds the top drive 200. The top drive 200 has a gripping means 301 for engaging the inner wall of ~~tubular 130~~the casing 15 and a motor 240 to rotate the ~~tubular 130~~casing 15. The motor 240 ~~rotates~~may rotate and threads the ~~tubular 130~~casing 15 into the ~~tubular~~casing string 210 ~~extending into~~16 held by the wellbore 180. The motor 240 can also rotate a drill string having a drill bit at an end, or for any other purposes requiring rotational movement of a tubular or a tubular string-spider 400. The gripping means 301 facilitate the engagement and disengagement of the casing 15 without having to thread and unthread the casing 15 to the top drive 200. Additionally, the top drive 200 is ~~shown with~~elevator 120 and a ~~coupled to~~a railing system 140 ~~coupled thereto~~. The railing system 140 prevents the top drive 200 from rotational movement during rotation of the ~~tubular~~casing string 21016, but allows for vertical movement of the top drive 200 under the ~~travelling~~traveling block 110.

[0008] In Figure 1B, the top drive 200 is shown engaged to tubular 130. The tubular 130 is positioned above the tubular string 210 located therebelow. With the tubular 130 positioned over the tubular string 210, the top drive 200 can lower and thread the tubular into the tubular string. Additionally, the spider 400, disposed in the platform 160, is shown engaged around a tubular string 210 that extends into wellbore 180.In Figure 1, the top drive 200 is shown engaged to casing 15. The casing 15 is placed in position below the top drive 200 by the elevator 120 in order for the top drive 200 to engage the casing 15. Additionally, the spider 400, disposed on the platform 160, is shown engaged around a casing string 16 that extends into wellbore 180. Once the casing 15 is positioned above the casing string 16, the top drive 200 can lower and thread the casing 15 into the casing string 16, thereby extending the length of the casing string 16. Thereafter, the extended casing string 16 may be lowered into the wellbore 180.

[0009] Figure 2 illustrates the top drive 200 engaged to the casing string 16 after the casing string 16 has been lowered through a spider 400. The spider 400 is shown disposed on the platform 160. The spider 400 comprises a slip assembly 440 including a set of slips 410 and piston 420. The slips 410 are wedge-shaped and constructed and arranged to slidably move along a sloped inner wall of the slip assembly 440. The slips 410 are raised or lowered by the

piston 420. When the slips 410 are in the lowered position, they close around the outer surface of the casing string 16. The weight of the casing string 16 and the resulting friction between the casing string 16 and the slips 410 force the slips downward and inward, thereby tightening the grip on the casing string 16. When the slips 410 are in the raised position as shown, the slips 410 are opened and the casing string 16 is free to move axially in relation to the slips 410. ~~a side view of a top drive engaged to a tubular, which has been lowered through a spider. As depicted in the Figure, the elevator 120 and the top drive 200 are connected to the travelling block 110 via a compensator 270. The compensator 270 functions similar to a spring to compensate for vertical movement of the top drive 200 during threading of the tubular 130 to the tubular string 210. In addition to its motor 240, the top drive includes a counter 250 to measure rotation of the tubular 130 during the time tubular 130 is threaded to tubular string 210. The top drive 200 also includes a torque sub 260 to measure the amount of torque placed on the threaded connection between the tubular 130 and the tubular string 210. The counter 250 and the torque sub 260 transmit data about the threaded joint to a controller via data lines (not shown). The controller is preprogrammed with acceptable values for rotation and torque for a particular joint. The controller compares the rotation and the torque data to the stored acceptable values.~~

~~[0010] Figure 2 also illustrates a spider 400 disposed in the platform 160. The spider 400 comprises a slip assembly 440, including a set of slips 410, and piston 420. The slips 410 are wedge-shaped and are constructed and arranged to slidably move along a slopped inner wall of the slip assembly 440. The slips 410 are raised or lowered by piston 420. When the slips 410 are in the lowered position, they close around the outer surface of the tubular string 210. The weight of the tubular string 210 and the resulting friction between the tubular string 210 and the slips 410, forces the slips downward and inward, thereby tightening the grip on the tubular string. When the slips 410 are in the raised position as shown, the slips are opened and the tubular string 210 is free to move axially in relation to the slips.~~

~~[0011] Figure 3 is cross-sectional view of a top drive 200 and a tubular 130 casing 15. The top drive 200 includes a gripping means 301 having a cylindrical~~

body 300, a wedge lock assembly 350, and slips 340 with teeth (not shown). The wedge lock assembly 350 and the slips 340 are disposed around the outer surface of the cylindrical body 300. The slips 340 are constructed and arranged to mechanically grip the inside of the ~~tubular 130~~casing 15. The slips 340 are threaded to piston 370 located in a hydraulic cylinder 310. The piston 370 is actuated by pressurized hydraulic fluid injected through fluid ports 320, 330. Additionally, springs 360 are located in the hydraulic cylinder 310 and are shown in a compressed state. When the piston 370 is actuated, the springs 360 decompress and assist the piston 370 in moving the slips 340 relative to the cylindrical body 300. The wedge lock assembly 350 is connected to the cylindrical body 300 and constructed and arranged to force the slips 340 against the inner wall of the ~~tubular 130 and moves with the cylindrical body 300~~casing 15.

[0012] In operation, the slips 340, and the wedge lock assembly 350 of top drive 200 are lowered inside ~~tubular 130~~the casing 15. Once the slips 340 are in the desired position within the ~~tubular 130~~casing 15, pressurized fluid is injected into the piston 370 through fluid port 320. The fluid actuates the piston 370, which forces the slips 340 towards the wedge lock assembly 350. The wedge lock assembly 350 functions to bias the slips 340 outwardly as the slips 340 are slidably forced along the outer surface of the assembly 350, thereby forcing the slips 340 to engage the inner wall of the ~~tubular 130~~casing 15.

[0013] Figure 4 illustrates a cross-sectional view of a top drive 200 engaged to ~~a tubular 130~~the casing 15. Particularly, the figure shows the slips 340 engaged with the inner wall of the ~~tubular 130~~casing 15 and a spring 360 in the decompressed state. In the event of a hydraulic fluid failure, the springs 360 can bias the piston 370 to keep the slips 340 in the engaged position, thereby providing an additional safety feature to prevent inadvertent release of the ~~tubular~~casing string ~~240~~16. Once the slips 340 are engaged with the ~~tubular 130~~casing 15, the top drive 200 can be raised along with the cylindrical body 300. By raising the body 300, the wedge lock assembly 350 will further bias the slips 340 outward. With the ~~tubular 130 engaged~~ casing 15 retained by the top drive

200, the top drive ~~can be relocated~~200 may relocate the casing 15 to align and thread the ~~tubular casing 15~~ with ~~tubular casing~~ string ~~240~~16.

[0014] In another embodiment (not shown), a top drive 200 includes a gripping means for engaging a ~~tubular casing~~ on the outer surface. For example, the slips of the ~~gripping means~~ can be arranged to grip on the outer surface of the ~~tubular casing~~, preferably gripping under the collar 380 of the ~~tubular 130 casing~~. In operation, the top drive is positioned over the desired ~~tubular casing~~. The slips are then lowered by the top drive to engage the collar 380 of the ~~tubular 130 casing~~. Once the slips are positioned beneath the collar 380, the piston is actuated to cause the slips to grip the outer surface of the ~~tubular 130~~. ~~Sensors may be placed in the slips to ensure that proper engagement of the tubular casing.~~

[0015] Figure 5 is a flow chart illustrating a typical operation of a ~~string or running casing assembly~~ using a top drive 200 and a spider 400. The flow chart relates to the operation of an apparatus generally illustrated in Figure 1B. At a first step 500, a ~~tubular casing~~ string ~~240~~16 is retained in a closed spider 400 and is thereby prevented from moving in a ~~downward~~an axial direction. At step 510, top drive 200 is moved to engage a ~~tubular 130 from a stack~~casing 15 with the aid of an elevator 120. ~~The tubular 130 may be a single tubular or could typically be made up of three tubulars threaded together to form a stack.~~ Engagement of the ~~tubular casing 15~~ by the top drive 200 includes grasping the ~~tubular casing 15~~ and engaging the inner surface thereof. At step 520, the top drive 200 moves the ~~tubular 130 casing 15~~ into position above the ~~tubular casing~~ string ~~240~~16 for connection therewith. At step 530, the top drive 200 threads the ~~tubular 130 casing 15~~ to ~~tubular casing~~ string ~~240~~16. At step 540, the spider 400 is opened and disengages the ~~tubular casing~~ string ~~240~~16. At step 550, the top drive 200 lowers the ~~tubular string 210, including tubular 130~~extended casing string 16 through the opened spider 400. At step 560 ~~and~~, the spider 400 is closed around the ~~tubular casing~~ string ~~240~~16. At step 570, the top drive 200 disengages the ~~tubular string casing string 16~~ and can proceed to add another ~~tubular 130 casing 15~~ to the ~~tubular casing~~ string ~~240~~16 as in step 510. The above-described steps may be utilized in ~~running to run~~ drill string in a drilling

~~operation or in running, to run casing to reinforce the wellbore or for assembling,~~
or to assemble run-in strings to place wellbore components in the wellbore. The steps may also be reversed in order to disassemble ~~the casing or a~~ tubular string.

[0016] Although the top drive is a good alternative to the Kelly and rotary table, the possibility of inadvertently dropping a ~~tubular~~casing string into the wellbore exists. As noted above, a top drive and spider must work in tandem, that is, at least one of them must engage the ~~tubular~~casing string at any given time during ~~tubular~~casing assembly. Typically, an operator located on the platform controls the top drive and the spider with manually operated levers that control fluid power to the slips that cause the top drive and spider to retain a ~~tubular~~casing string. At any given time, an operator can inadvertently drop the ~~tubular~~casing string by moving the wrong lever. Conventional interlocking systems have been developed and used with elevator/spider systems to address this problem, but there remains a need for a workable interlock system usable with a top drive/spider system such as the one described herein.

[0017] There is a need therefore, for an interlock system for use with a top drive and spider to prevent inadvertent release of a tubular string. There is a further need for an interlock system to prevent the inadvertent dropping of a tubular or tubular string into a wellbore. There is also a need for an interlock system that prevents a spider or a top drive from disengaging a tubular string until the other component has engaged the tubular.

SUMMARY OF THE INVENTION

[0018] The present invention generally provides an apparatus and methods to prevent inadvertent release of a tubular or tubular string. In one aspect, the apparatus and methods disclosed herein ensure that either the top drive or the spider is engaged to the tubular before the other component is disengaged from the tubular. The interlock system is utilized with a spider and a top drive during assembly of a tubular string.

[0018.1] In another aspect, the present invention provides an apparatus for use

with tubulars. The apparatus includes a first device for gripping and joining the tubulars, a second device for gripping the tubulars, and an interlock system to ensure that the tubulars are gripped by at least one of the first or second device.

[0018.2] In another aspect still, the present invention provides a method for assembling and disassembling tubulars. The method includes joining a first tubular engaged by a first apparatus to a second tubular engaged by a second apparatus thereby forming a tubular string. An interlock system is provided to ensure that at least one of the first apparatus or the second apparatus is engaging the tubular string. After the tubulars are joined, the second apparatus is opened to disengage the string, thereby allowing the tubular string to be lowered through the second apparatus. After the string is repositioned, the second apparatus is actuated to re-engage the tubular string. After the second apparatus secures the tubular string, the first apparatus is disengaged from the string.

[0018.3] In another aspect still, the first apparatus includes a gripping member for engaging the tubular. In one aspect, the gripping member is movably coupled to the first apparatus. Particularly, the gripping member may pivot relative to the first apparatus to facilitate engagement with the tubular. In one embodiment, a swivel is used to couple the gripping member to the first apparatus.

BRIEF DESCRIPTION OF THE DRAWINGS

[0019] So that the manner in which the above recited features, advantages and objects of the present invention are attained and can be understood in detail, a more particular description of the invention, briefly summarized above, may be had by reference to the embodiments thereof which are illustrated in the appended drawings.

[0020] It is to be noted, however, that the appended drawings illustrate only typical embodiments of this invention and are therefore, not to be considered limiting of its scope, for the invention may admit to other equally effective embodiments.

[0021] ~~Figure 4A is~~ 1 shows a side view of a drilling rig 100 having a top drive 200 and an elevator 120 configured to connect tubulars.

[0022] ~~Figure 1B is a side view of a drilling rig 100 having a top drive 200, an elevator 120, and a spider 400.~~

[0023] ~~Figure 2 illustrates a side view of a~~ the top drive engaged to a tubular, which that has been lowered through a spider.

[0024] ~~Figure 3 is a cross-sectional view of a top drive 200 and a tubular 130 gripping member for use with a top drive for handling tubulars in the un-engaged position.~~

[0025] ~~Figure 4 illustrates a cross-sectional view of a top drive 200 the gripping member of Figure 3 in the engaged to a tubular 130 position.~~

[0026] ~~Figure 5 is a flow chart of a typical operation of tubular string or casing assembly for connecting tubulars using a top drive and a spider.~~

[0027] ~~Figure 6 shows a flow chart for connecting tubulars using an interlock system for a spider and a top drive according to aspects of the present invention.~~

[0028] ~~Figure 7 illustrates the mechanics of the interlock system in use with a spider, a top drive and a controller an apparatus for connecting tubulars according to aspects of the present invention. The top drive is shown before it has engaged the tubular.~~

[0029] ~~Figure 8 illustrates the top drive of Figure 7 after it has engaged the tubular.~~

[0029.1] ~~Figure 9 illustrates the top drive of Figure 7 after it has lowered the tubular toward the rig floor.~~

[0029.2] ~~Figure 10 illustrates the mechanics of the interlock system in use with a spider, a top drive and a controller according to aspects of the present invention.~~

[0029.3] Figure 11 illustrates a control plate for a spider lever and a top drive lever according to aspects of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0030] The present invention is an interlock system for use with a top drive and a spider during assembly of a string of tubulars. The invention may be utilized to assemble tubulars for different purposes including drill strings, strings of liner and casing and run-in strings for wellbore components.

[0031] Figure 6 is a flow chart illustrating the use of an interlock system 700 of the present invention with a spider 400 and a top drive 200, and Figure 710 illustrates the mechanics of the interlock system 700 in use with a spider 400, a top drive 200, and a controller 900. At step 500, a ~~tubular~~casing string 210 is retained in a closed spider 400 and prevented from moving in ~~a downward~~an axial direction. ~~The, as illustrated in Figure 8. In one embodiment, the spider 400 is a flush mounted spider that is disposed in the platform 160. Referring to Figure 10, the spider 400 includes a spider piston sensor 990 located at a spider piston 420 to sense when the spider 400 is open or closed around the tubular~~casing string 210. The sensor data 502 is relayed to a controller 900.

[0032] A controller 900 includes a programmable central processing unit that is operable with a memory, a mass storage device, an input control unit, and a display unit. Additionally, the controller 900 includes well-known support circuits such as power supplies, clocks, cache, input/output circuits and the like. The controller 900 is capable of receiving data from sensors and other devices and capable of controlling devices connected to it.

[0033] One of the functions of the controller 900 is to prevent opening of the spider 400. Preferably, the spider 400 is locked in the closed position by a solenoid valve 980 (~~Figure 7~~) that is placed in the control line between the manually operated spider control lever 630 (~~Figure 7~~) and the source of fluid power operating the spider 400. Specifically, the spider solenoid valve 980 controls the flow of fluid to the spider piston 420. The solenoid valve 980 is

operated by the controller 900, and the controller 900 is programmed to keep the valve 980 closed until certain conditions are met. While valve 980 is electrically powered in the embodiment described herein, the valve 980 could be fluidly or pneumatically powered so long as it is controllable by the controller 900. Typically, the valve 980 is closed and the spider 400 is locked until a tubular 130 is successfully joined to the string 210 and held by the top drive 200.

[0034] At step 510, the top drive 200 is moved to engage a casing 130. Referring back to Figure 7, the elevator 120 is coupled to the top drive 200 using a piston and cylinder assembly 122 and a pair of bails 124. The piston and cylinder assembly 122 may serve to axially translate the elevator 120 relative to the gripping means 301 of the top drive 200. As shown, the gripping means 301, also known as a gripping head, is an internal gripping apparatus, wherein it may be inserted into the casing 130 to engage an interior surface thereof. In one embodiment, a pivotable mechanism 125 is employed to facilitate the engagement of the gripping means 301 to the casing 130. An example of a suitable pivotable mechanism 125 includes a swivel 125 having a first portion 125A pivotable relative to a second portion 125B. The swivel 125 couples the gripping means 301 to the top drive 200 and allows the gripping means 301 to move or pivot relative thereto. Particularly, first and second portions 125A, 125B include connections means for connecting to the top drive 200 and the gripping means 301, respectively. Preferably, the pivotable mechanism 125 includes a bore therethrough for fluid communication between the top drive 200 and the gripping means 301. pre-assembled tubular 130 from a stack with the aid of an elevator 120. A top drive sensor 995 (Fig. 7) is placed near a top drive piston 370 to sense when the top drive 200 is disengaged, or in this case engaged around the tubular 130. The sensor data 512 is relayed to the controller 900. At step 520, the top drive 200 moves the tubular 130 into position and alignment above the tubular string 210. At step 530, the top drive 200 rotationally engages the tubular 130 to tubular string 210, creating a threaded joint therebetween. Torque data 532 from a torque sub 260 and rotation data 534 from a counter 250 are sent to the controller 900.

~~[0035] The controller 900 is preprogrammed with acceptable values for rotation and torque for a particular connection. The controller 900 compares the rotation data 534 and the torque data 532 from the actual connections and determines if they are within the accepted values. If not, then the spider 400 remains locked and closed, and the tubular 130 can be rethreaded or some other remedial action can take place by sending a signal to an operator. If the values are acceptable, the controller 900 locks the top drive 200 in the engaged position via a top drive solenoid valve 970 (Fig. 7) that prevents manual control of the top drive 200. At step 540, the controller 900 unlocks the spider 400 via the spider solenoid valve, and allows fluid to power the piston 420 to open the spider 400 and disengage it from the tubular string 210. At step 550, the top drive 200 lowers the tubular string 210, including tubular 130 through the opened spider 400. At step 560 and the spider 400 is closed around the tubular string 210. The spider sensor 990 (Fig. 7) signals the controller 900 that the spider 400 is closed. If no signal is received, then the top drive 200 stays locked and engaged to tubular string 210. If a signal is received confirming that the spider is closed, the controller locks the spider 400 in the closed position, and unlocks the top drive 200. At step 570 the top drive 200 can disengage the tubular string 210 and proceed to add another tubular 130. In this manner, at least the top drive or the spider is engaging the tubular string at all times.~~

[0035.1] To engage the casing 130, the piston and cylinder assembly 122 is actuated to position the elevator 120 proximate the casing 130. The elevator 120 is then disposed around the casing 130. The movable bails 124 allow the casing 130 to tilt toward the well center. Thereafter, the gripping means 301 may be pivoted into alignment with the casing 130 for insertion thereof. Particularly, the swivel 125 is actuated to pivot the gripping means 301 as illustrated in Figure 7. Once aligned, the gripping means 301 is inserted into the casing 130, and the slips 340 are actuated to engage the interior of the casing 130.

[0035.2] In one aspect, a top drive sensor 995 (Figure 10) is placed near a top drive piston 370 to determine whether the gripping means 301 is engaged with the casing 130. The sensor data 512 is relayed to the controller 900 for processing.

[0035.3] At step 520, the top drive 200 moves the casing 130 into position above the casing string 210. Particularly, the swivel 125 is actuated to pivot the gripping means 301 toward the well center. In turn, the casing 130 is also positioned proximate the well center, and preferably, into alignment with the casing string 210 in the spider 400. Additionally, the traveling block 110 is actuated to lift the top drive 200 and the attached casing 130. In this manner, the casing 130 is aligned with the casing string 210 in the spider 400, as illustrated in Figure 8.

[0035.4] At step 530, the top drive 200 rotationally engages the casing 130 to the casing string 210, thereby creating a threaded joint therebetween. In one embodiment, the top drive 200 may include a counter 250. The counter 250 is constructed and arranged to measure the rotation of the casing 130 during the make up process. The top drive 200 may also be equipped with a torque sub 260 to measure the amount of torque placed on the threaded connection. Torque data 532 from the torque sub 260 and rotation data 534 from the counter 250 are sent to the controller 900 for processing. The controller 900 is preprogrammed with acceptable values for rotation and torque for a particular connection. The controller 900 compares the rotation data 534 and the torque data 532 from the actual connections and determines if they are within the accepted values. If not, then the spider 400 remains locked and closed, and the casing 130 can be re-threaded or some other remedial action can take place by sending a signal to an operator. If the values are acceptable, the controller 900 locks the top drive 200 in the engaged position via a top drive solenoid valve 970 (Fig. 10) that prevents manual control of the top drive 200.

[0035.5] At step 540, the controller 900 unlocks the spider 400 via the spider solenoid valve 980, and allows fluid to power the piston 420 to open the spider 400 and disengage it from the casing string 210. At step 550, the top drive 200 lowers the casing string 210, including casing 130, through the opened spider 400. Figure 9 shows the casing 130 lowered by the top drive 200.

[0035.6] At step 560, the spider 400 is closed around the casing string 210. At step 562, the spider sensor 990 (Fig. 10) signals to the controller 900 that the spider 400 is closed. If a signal is received confirming that the spider 400 is

closed, the controller 900 locks the spider 400 in the closed position, and unlocks the top drive 200. If no signal is received, the top drive 200 stays locked and engaged to casing string 210. At step 570, after a signal is received, the top drive 200 disengages the casing string 210 and may proceed to add another casing 130. In this manner, at least the top drive 200 or the spider 400 is engaging the casing string 210 at all times.

[0036] Alternatively, or in addition to the foregoing, a compensator 270 (~~shown in Figure 2~~) may be utilized to gather additional information about the joint formed between the tubular and the tubular string. In one aspect, the compensator 270 couples the top drive 200 to the traveling block 110. The compensator 270 may function similar to a spring to compensate for vertical movement of the top drive 200 during threading of the casing 130 to the casing string 210. The compensator 270, in addition to allowing incremental movement of the top drive 200 during threading together of the tubulars, may be used to ensure that a threaded joint has been made and that the tubulars are mechanically connected together. For example, after a joint has been made between the tubular and the tubular string, the top drive may be raised or pulled up. If a joint has been formed between the tubular and the string, the compensator will “stoke out” completely, due the weight of the tubular string therebelow. If however, a joint has not been formed between the tubular and the string due to some malfunction of the top drive or misalignment between a tubular and a tubular string therebelow, the compensator will stroke out only a partial amount due to the relatively little weight applied thereto by the single tubular or tubular stack. A stretch sensor located adjacent the compensator, can sense the stretching of the compensator 270 and can relay the data to a controller 900. Once the controller 900 processes the data and confirms that the top drive is engaged to a complete tubular string, the top drive 200 is locked in the engaged position, and the next step 540 can proceed. If no signal is received, then the spider 400 remains locked and a signal maybe transmitted by the controller to an operator. During this “stretching” step, the spider 400 is not required to be unlocked and opened. The spider 400 and the slips 410 are constructed and arranged to prevent downward movement of the string but allow the ~~tubular~~ casing string 210 to be lifted up and moved axially in a

vertical direction even though the spider is closed. When closed, the spider 400 will not allow the ~~tubular~~casing string 210 to fall through its slips 410 due to friction and the shaped of the teeth on the spider slips.

[0037] The interlock system ~~500~~700 is illustrated in Figure ~~7~~10 with the spider 400, the top drive 200, and the controller 900 including various control, signal, hydraulic, and sensor lines. The top drive 200 is shown engaged to a ~~tubular~~casing string 210 and is coupled to a railing system 140. The railing system 140 includes wheels 142 allowing the top drive 200 to move axially. The spider 400 is shown disposed in the platform 160 and in the closed position around the ~~tubular~~casing string 210. The spider 400 and the top drive 200 may be pneumatically actuated, however the spider 400 and top drive 200 discussed herein are hydraulically activated. Hydraulic fluid is supplied to a spider piston 420 via a spider control valve 632. The spider control valve 632 is a three-way valve and is operated by a spider lever 630.

[0038] Also shown in Figure ~~7~~10 is a sensor assembly 690 with a piston 692 coupled to spider slips 410 to detect when the spider 400 is open or closed. The sensor assembly 690 is in communication with a locking assembly 660, which along with a control plate 650 prevents the movement of the spider 400 and top drive lever. The locking assembly 660 includes a piston 662 having a rod 664 at a first end. The rod 664 when extended, blocks the movement of the control plate 650 when the plate is in a first position. When the spider 400 is in the open position, the sensor assembly 690 communicates to the locking assembly 660 to move the rod 664 to block the control plate's 650 movement. When the spider 400 is in the closed position as shown, the rod 664 is retracted allowing the control plate 650 to move freely from the first to a second position. Additionally, the sensor assembly 660 can also be used with the top drive 200 as well in the same fashion. Similarly, hydraulic fluid is supplied to a top drive piston 370 via a top drive control valve 642 and hydraulic lines. The top drive control valve 642 is also a three-way valve and is operated by a top drive lever 640. A pump 610 is used to circulate fluid to the respective pistons 370, 420. A reservoir 620 is used to re-circulate hydraulic fluid and receive excess fluid. Excess gas in the reservoir 620 is vented 622.

[0039] Further shown in Figure 710, controller 900 collects data from a top drive sensor 995 regarding the engagement of the top drive to the tubularcasing string 210. Data regarding the position of the spider 400 is also provided to the controller 900 from a spider sensor 990. The controller 900 controls fluid power to the top drive 200 and spider 400 via solenoid valves 970, 980, respectively.

[0040] In Figure 710, the top drive 200 is engaged to tubularcasing string 210 while the spider 400 is in the closed position around the same tubularcasing string 210. At this point, steps 500, 510, 520, and 530 of Figure 6 have occurred. Additionally, the controller 900 has determined through the data received from counter 250 and torque sub 260 that an acceptable threaded joint has been made between tubularcasing 130 and tubularcasing string 210. In the alternative or in addition to the foregoing, a compensator 270 can also provide data to the controller 900 that a threaded joint has been made and that the tubularcasing 130 and the tubularcasing string 210 are mechanically connected together via a stretch sensor (not shown). The controller 900 then sends a signal to a solenoid valve 970 to lock and keep a top drive piston 370 in the engaged position within the tubularcasing string 210. Moving to step 540 (figure 6), the controller 900 can unlock the previously locked spider 400, by sending a signal to a solenoid valve 980. The spider 400 must be unlocked and opened in order for the top drive 200 to lower the tubularcasing string 210 through the spider 400 and into a wellbore. An operator (not shown) can actuate a spider lever 630 that controls a spider valve 632, to allow the spider 400 to open and disengage the tubularcasing string 210. When the spider lever 630 is actuated, the spider valve 632 allows fluid to be flow to spider piston 420 causing spider slips 410 to open. With the spider 400 opened, a sensor assembly 690 in communication with a locking assembly 660 will cause a rod 664 to block the movement of a control plate 650. Because the plate 650 will be blocked in the rightmost position, the top drive lever 640 is held in the locked position and will be unable to move to the open position.

[0041] As illustrated in Figure 710, the interlock system 700 when used with the top drive 200 and the ~~spiders~~spider 400 prevents the operator from inadvertently dropping the tubularcasing string 210 into the wellbore. As disclosed herein, the ~~tubular string~~casing string 210 at all times is either engaged

by the top drive 200 or the spider 400. Additionally, the controller ~~prevents~~900 may prevent operation of the top drive 200 under certain situations, even if the top drive control lever 640 is actuated. ~~Further—~~In another aspect, the interlock system ~~provides~~700 may include a control plate 650 to control the physical movement of levers 630, 640 between anthe open and closed positions, thereby preventing the operator from inadvertently actuating the wrong lever.

[0042] Figure 811 illustrates a control plate 650 for a spider lever 630 and a top drive lever 640 that can be used with the interlock system 700 of the present invention. The control plate 650 is generally rectangular in shape and is provided with a series of slots 656 to control the movement of the spider lever 630, and the top drive lever 640. Typically, the control plate 650 is slideably mounted within a box 652. The slots 656 define the various positions in which the levers 630, 640 may be moved at various stages of the tubular assembly or disassembly. The levers 630, 640 can be moved in three positions: (1) a neutral position located in the center; (2) a closed position located at the top and causes the slips to close; and (3) an open position located at the bottom, which causes the slips to open. The control plate 650 can be moved from a first rightmost position to a second leftmost position with a knob 654. However, both levers 630, 640 must be in the closed position before the control plate is moved from one position to another. The control plate 650 is shown in the first rightmost position with a rod 664 extending from a locking assembly 660 to block the movement of the control plate. In operation, in the first rightmost position of the control plate 650, the spider lever 630 can be moved between the open and close positions, while the top drive lever 640 is kept in the closed position. In the second leftmost position, the top drive lever 640 can be moved between the open and close positions, while the spider lever 630 is kept in the closed position. A safety lock 658 is provided to allow the top drive or spider levers 630, 640 to open and override the control plate 650 when needed.

[0043] The interlock system 700 may be any interlock system that allows a set of slips to disengage only when another set of slips is engaged to the tubular. The interlock system 700 may be mechanically, electrically, hydraulically, pneumatically actuated systems. The spiderspider 400 may be any spider that

functions to hold a tubular or a tubular string at the surface of the wellbore. A top ~~drive~~drive 200 may be any system that ~~can grab~~includes a gripping means for retaining a tubular by the inner or outer surface and can rotate the retained tubular. The gripping means may include an internal gripping apparatus such as a spear, an external gripping apparatus such as a torque head, or any other gripping apparatus for gripping a tubular as known to a person of ordinary skill in the art. For example, the external gripping apparatus may include a sensor for detecting information from its slips to ensure proper engagement of the casing. The top ~~drive~~drive 200 can also be hydraulically or pneumatically activated.

[0044] While the foregoing is directed to the preferred embodiment of the present invention, other and further embodiments of the invention may be devised without departing from the basic scope thereof, and the scope thereof is determined by the claims that follow.

ABSTRACT OF THE DISCLOSURE

The present invention provides for an apparatus and methods to prevent an operator from inadvertently dropping a string into a wellbore during assembling and disassembling of tubulars. Additionally, the apparatus and methods can be used to for running in casing, running in wellbore components or for a drill string.